

# PAINTING TAPE GUIDE

	Shurtape®			Painter's Mate® BRAND			FROGTAPE®			
	CP 66®	CP 27®	CF 33	Painter's Mate® Green®	Painter's Mate® Ultra™	Double-Sided Poly-Hanging Tape	FrogTape® Pro Grade Orange	FrogTape® Pro Grade	FrogTape® Multi-Surface	FrogTape® Delicate
Adhesion Strength	High	Medium	Medium	Medium	Medium	Medium (Non-Liner Side)	High	Medium	Medium	Light
Clean Removal Time (Days) with No/Indirect Sunlight Exposure	3	14	21	8	14	21 (Non-Liner Side)	3	14	21	60
Clean Removal Time (Days) with Direct Sunlight Exposure	1	14	1	8	14	7	1	14	7	60
<b>DELICATE SURFACES (COATED OR UNCOATED)</b>										
Fresh Paint (Minimum 24 hours old)										*
Wallpapers All Types#										*
Laminate & Veneer Wood Cabinets Melamine										*
<b>PAINTED/COATED SURFACES* (PRIMER, PAINT, ENAMEL, VARNISH, OR ACRYLIC)</b>										
Hard-to-Stick-to Paints		*			*			*	*	
Smooth Wallboard/Plasterboard Metal Fixtures & Joinery Woodwork Doors Windows & Trim	*	*	*	*	*	*	*	*	*	*
Rough Bricks Concrete Wall with Orange Peel/Knockdown Texture	*						*			
<b>UNCOATED/OTHER SURFACES</b>										
Carpet & Fabrics	*	*		*	*	*	*	*	*	
Hanging Poly-Sheeting						*				
Smooth Glass Plastics Porcelain Countertops Caulk (cured until firm) Doors Fixtures & Hardware Siding & Windows Metals Vinyl Base Molding, Window & Door Trim	*	*	*	*	*	*	*	*	*	*
Rough Brick Concrete Grout Mortar Stucco	*						*			
<b>APPLICATION CONDITIONS</b>										
Normal Temperatures (50 – 100°F)	*	*	*	*	*	*	*	*	*	*
Warm Temperatures (100 – 120°F)							*			
Elevated Humidity							*			
<b>SUPER SHARP PAINT LINES</b>								*	*	*

**Shurtape**  
TECHNOLOGIES

\* Fully cured coatings over 30 days old. To determine if paint is cured, see manufacturer's recommendation for time interval before fresh paint surface can be washed.  
#Wall coverings vary greatly so it's important to test tape removability on an inconspicuous area before application.  
Note: This table is offered as a guide only. It is the user's responsibility to determine the suitability of the product for its intended use.

©Shurtape Technologies, LLC 2020/81848